

DEPARTMENT OF TRANSPORTATION  
FEDERAL AVIATION ADMINISTRATION  
WASHINGTON, D.C.

Revision: 4  
Date: 11/14/96

M A S T E R   M I N I M U M   E Q U I P M E N T   L I S T

CESSNA - (TURBOPROP) 421C STC SA1361SO

Federal Aviation Administration  
AIRCRAFT EVALUATION GROUP, MKC-AEG  
1201 WALNUT ST. SUITE 900  
Kansas City, Missouri 64106

Telephone: (816) 426-3946  
FAX: (816) 426-3084

FEDERAL AVIATION ADMINISTRATION  
MASTER MINIMUM EQUIPMENT LIST

Page: I  
Revision: 4  
Date: 11/14/96

CESSNA - (TURBOPROP) 421C STC SA1361SO

Table of Contents

SYSTEM NO.	SYSTEM	PAGE
--	Table of Contents	I
--	Log of Revisions	II
--	Control Page	III, IV
--	Highlights of Change	V, VI
--	Definitions	VII, VIII, IX, X
--	Definitions	XI, XII, XIII, XIV
--	Preamble	XV, XVI
--	Guidelines for (O) & (M) Procedures	XVII, XVIII
21	Air Conditioning	21-1, 2
22	Auto Flight	22-1
23	Communications	23-1
24	Electrical Power	24-1
25	Equipment/Furnishings	25-1, 2
26	Fire Protection	26-1
27	Flight Controls	27-1
28	Fuel	28-1
30	Ice and Rain Protection	30-1
31	Indicating/Recording Systems	31-1
33	Lights	33-1, 2
34	Navigation	34-1, 2, 3, 4, 5
34	Navigation	34-6
35	Oxygen	35-1
52	Doors	52-1
61	Propellers	61-1

FEDERAL AVIATION ADMINISTRATION  
MASTER MINIMUM EQUIPMENT LIST

Page: II  
Revision: 4  
Date: 11/14/96

CESSNA - (TURBOPROP) 421C STC SA1361SO

Log of Revisions

REV.NO.	DATE	PAGE NUMBERS	INITIALS
ORIGINAL	08/01/83		
1	11/20/87	ALL PAGES	
2	05/05/89	ALL PAGES	
3	06/22/89	HIGHLIGHTS OF REV.,DEFINITIONS	
3	06/22/89	PREAMBLE	
3a	04/17/91	HIGHLIGHTS OF REV.,DEFINITIONS	
3a	04/17/91	23-1	
3b		25-1,25-2,26-1,27-1,28-1	
3b		30-1,31-1,33-1,33-2,34-1	
3b		34-2,34-3,34-4,34-5,34-6	
3b		35-1,52-1,61-1	
4	11/14/96	HIGHLIGHTS OF REV.,DEFINITIONS	
4	11/14/96	GUIDELINES	
4	11/14/96	21-1,21-2,22-1,23-1,24-1	
4	11/14/96	25-1,25-2,26-1,27-1,28-1	
4	11/14/96	30-1,31-1,33-1,33-2,34-1	
4	11/14/96	34-2,34-3,34-4,34-5,34-6	
4	11/14/96	35-1,52-1,61-1	

FEDERAL AVIATION ADMINISTRATION  
MASTER MINIMUM EQUIPMENT LIST

Page: III  
Revision: 4  
Date: 11/14/96

CESSNA - (TURBOPROP) 421C STC SA1361SO

Control Page

SYSTEM	PAGE	REV NO.	CURRENT DATE
Cover Page	-	4	11/14/96
Table of Contents	I	4	11/14/96
Log of Revisions	II	4	11/14/96
Control Page	III	4	11/14/96
	IV	4	11/14/96
Highlights of Change	V	4	11/14/96
	VI	4	11/14/96
Definitions	VII	6	01/31/95
	VIII	6	01/31/95
	IX	6	01/31/95
	X	6	01/31/95
	XI	6	01/31/95
	XII	6	01/31/95
	XIII	6	01/31/95
	XIV	6	01/31/95
Preamble	XV	2	06/14/89
	XVI	2	06/14/89
Guidelines for (O) & (M) Procedures	XVII	4	11/14/96
	XVIII	4	11/14/96
21	21-1	4	11/14/96
	21-2	4	11/14/96
22	22-1	4	11/14/96
23	23-1	4	11/14/96
24	24-1	4	11/14/96
25	25-1	4	11/14/96
	25-2	4	11/14/96
26	26-1	4	11/14/96
27	27-1	4	11/14/96
28	28-1	4	11/14/96
30	30-1	4	11/14/96
31	31-1	4	11/14/96
33	33-1	4	11/14/96
	33-2	4	11/14/96
34	34-1	4	11/14/96
	34-2	4	11/14/96
	34-3	4	11/14/96
	34-4	4	11/14/96
	34-5	4	11/14/96
	34-6	4	11/14/96
35	35-1	4	11/14/96

FEDERAL AVIATION ADMINISTRATION  
MASTER MINIMUM EQUIPMENT LIST

Page: IV  
Revision: 4  
Date: 11/14/96

CESSNA - (TURBOPROP) 421C STC SA1361SO

Control Page

SYSTEM	PAGE	REV NO.	CURRENT DATE
52	52-1	4	11/14/96
61	61-1	4	11/14/96

CESSNA - (TURBOPROP) 421C STC SA1361SO

Highlights of Change

All asterisks representing placarding requirements have been removed.  
See Definitions section, item 4 for placarding requirements.

The term "May be inoperative" has been removed in column 4 if that was the only proviso. By its inclusion in the MMEL, the item has relief for being inoperative.

ATA #	Remarks
23-4	Changed relief in accordance with Policy Letter 9 designated as Global Change 13.
23-6	Added relief for Boom Microphones in accordance with Policy Letter 58 designated as Global Change 14.
25-1	Changed relief for standardization.
25-2	Deleted the maintenance procedure requirement.
25-3	Changed relief for operator flexibility.
25-4	Changed relief for standardization.
25-5	Added relief for First Aid Kits in accordance with Policy Letter 73 designated as Global Change 17.
26-1	Changed relief in accordance with Policy Letter 75 designated as Global Change 19.
30-1	Changed relief for standardization.
33-1	Changed relief in accordance with Policy Letter 77 designated as Global Change 21.
33-2	Changed relief for standardization.
33-10	Changed relief in accordance with Policy Letter 37.

FEDERAL AVIATION ADMINISTRATION  
MASTER MINIMUM EQUIPMENT LIST

Page: VI  
Revision: 4  
Date: 11/14/96

CESSNA - (TURBOPROP) 421C STC SA1361SO

Highlights of Change

ATA #	Remarks
34-1	Changed relief for standardization.
34-2	Changed relief for standardization.
34-3	Changed relief for standardization.
34-4	Changed relief for clarity.
34-5	Changed relief for standardization.
34-6	Changed relief for clarity.
34-7	Changed relief in accordance with Policy Letter 76 designated as Global Change 20.
34-8	Added relief for GPS.
34-18	Added relief for Altitude Alerter.
34-20	Added relief for Traffic Alert Collision Avoidance System (TCAS II)
34-21	Added relief for Traffic Alert Collision Avoidance System (TCAS I)
34-22	Added relief for Ground Proximity Warning System (GPWS).
34-23	Added relief for Flight Profile Advisory System.

CESSNA - (TURBOPROP) 421C STC SA1361SO

#### Definitions

#### 1. System Definitions.

System numbers are based on the Air Transport Association (ATA) Specification Number 100 and items are numbered sequentially.

- a. "Item" (Column 1) means the equipment, system, component, or function listed in the "Item" column.
- b. "Number Installed" (Column 2) is the number (quantity) of items normally installed in the aircraft. This number represents the aircraft configuration considered in developing this MMEL. Should the number be a variable (e.g., passenger cabin items) a number is not required.
- c. "Number Required for Dispatch" (Column 3) is the minimum number (quantity) of items required for operation provided the conditions specified in Column 4 are met.

NOTE: Where the MMEL shows a variable number required for dispatch, the MEL must reflect the actual number required for dispatch or an alternate means of configuration control approved by the Administrator.

- d. "Remarks or Exceptions" (Column 4) in this column includes a statement either prohibiting or permitting operation with a specific number of items inoperative, provisos (conditions and limitations) for such operation, and appropriate notes.
- e. A vertical bar (change bar) in the margin indicates a change, addition or deletion in the adjacent text for the current revision of that page only. The change bar is dropped at the next revision of that page.

2. "Airplane/Rotorcraft Flight Manual" (AFM/RFM) is the document required for type certification and approved by the responsible FAA Aircraft Certification Office. The FAA approved AFM/RFM for the specific aircraft is listed on the applicable Type



CESSNA - (TURBOPROP) 421C STC SA1361SO

#### Definitions

Certificate Data Sheet.

3. "As required by FAR" means that the listed item is subject to certain provisions (restrictive or permissive) expressed in the Federal Aviation Regulations operating rules. The number of items required by the FAR must be operative. When the listed item is not required by FAR it may be inoperative for time specified by repair category.

4. Each inoperative item must be placarded to inform and remind the crewmembers and maintenance personnel of the equipment condition.

NOTE: To the extent practical, placards should be located adjacent to the control or indicator for the item affected; however, unless otherwise specified, placard wording and location will be determined by the operator.

5. "-" symbol in Column 2 and/or Column 3 indicates a variable number (quantity) of the item installed.

6. "Deleted" in the remarks column after a sequence item indicates that the item was previously listed but is now required to be operative if installed in the aircraft.

7. "ER" refers to extended range operations of a two-engine airplane which has a type design approval for ER operations and complies with the provisions of Advisory Circular 120-42A.

8. "Federal Aviation Regulations" (FAR) means the applicable portions of the Federal Aviation Act and Federal Aviation Regulations.

9. "Flight Day" means a 24 hour period (from midnight to midnight) either Universal Coordinated Time (UCT) or local time, as established by the operator, during which at least one flight is initiated for the affected aircraft.

10. "Icing Conditions" means an atmospheric environment that may cause ice to form on the aircraft or in the engine(s).

11. Alphabetical symbol in Column 4 indicates a proviso (condition or limitation) that must be complied with for

CESSNA - (TURBOPROP) 421C STC SA1361SO

#### Definitions

operation with the listed item inoperative.

12. "Inoperative" means a system and/or component malfunction to the extent that it does not accomplish its intended purpose and/or is not consistently functioning normally within its approved operating limit(s) or tolerance(s).

13. "Notes:" in Column 4 provides additional information for crewmember or maintenance consideration. Notes are used to identify applicable material which is intended to assist with compliance, but do not relieve the operator of the responsibility for compliance with all applicable requirements. Notes are not a part of the provisos.

14. Inoperative components of an inoperative system: Inoperative items which are components of a system which is inoperative are usually considered components directly associated with and having no other function than to support that system. (Warning/caution systems associated with the inoperative system must be operative unless relief is specifically authorized per the MMEL).

15. "(M)" symbol indicates a requirement for a specific maintenance procedure which must be accomplished prior to operation with the listed item inoperative. Normally these procedures are accomplished by maintenance personnel; however, other personnel may be qualified and authorized to perform certain functions. Procedures requiring specialized knowledge or skill, or requiring the use of tools or test equipment should be accomplished by maintenance personnel. The satisfactory accomplishment of all maintenance procedures, regardless of who performs them, is the responsibility of the operator. Appropriate procedures are required to be published as part of the operator's manual or MEL.

16. "(O)" symbol indicates a requirement for a specific operations procedure which must be accomplished in planning for and/or operating with the listed item inoperative. Normally these procedures are accomplished by the flight crew; however, other personnel may be qualified and authorized to perform certain functions. The satisfactory accomplishment of all procedures, regardless of who performs them, is the responsibility of the operator. Appropriate procedures are

FEDERAL AVIATION ADMINISTRATION  
MASTER MINIMUM EQUIPMENT LIST

Page: X  
Revision: 6  
Date: 01/31/95

CESSNA - (TURBOPROP) 421C STC SA1361SO

Definitions

required to be published as a part of the operator's manual or MEL.

NOTE: The (M) and (O) symbols are required in the operator's MEL unless otherwise authorized by the Administrator.

17. "Deactivated" and "Secured" means that the specified component must be put into an acceptable condition for safe flight. An acceptable method of securing or deactivating will be established by the operator.

18. "Visual Flight Rules" (VFR) is as defined in FAR Part 91. This precludes a pilot from filing an Instrument Flight Rules (IFR) flight plan.

19. "Visual Meteorological Conditions" (VMC) means the atmospheric environment is such that would allow a flight to proceed under the visual flight rules applicable to the flight. This does not preclude operating under Instrument Flight Rules.

20. "Visible Moisture" means an atmospheric environment containing water in any form that can be seen in natural or artificial light; for example, clouds, fog, rain, sleet, hail, or snow.

21. "Passenger Convenience Items" means those items related to passenger convenience, comfort or entertainment such as, but not limited to, galley equipment, movie equipment, ash trays, stereo equipment, overhead reading lamps, etc.

22. Repair Intervals: All users of an MEL approved under FAR 121, 125, 129 and 135 must effect repairs of inoperative systems or components, deferred in accordance with the MEL, at or prior to the repair times established by the following letter designators:

Category A. Items in this category shall be repaired within the time interval specified in the remarks column of the operator's approved MEL.

Category B. Items in this category shall be repaired within three (3) consecutive calendar days (72 hours), excluding the day the malfunction was recorded in the aircraft maintenance

CESSNA - (TURBOPROP) 421C STC SA1361SO

Definitions

record/logbook. For example, if it were recorded at 10 a.m. on January 26th, the three day interval would begin at midnight the 26th and end at midnight the 29th.

Category C. Items in this category shall be repaired within ten (10) consecutive calendar days (240 hours), excluding the day the malfunction was recorded in the aircraft maintenance record/logbook. For example, if it were recorded at 10 a.m. on January 26th, the 10 day interval would begin at midnight the 26th and end at midnight February 5th.

Category D. Items in this category shall be repaired within one hundred and twenty (120) consecutive calendar days (2880 hours), excluding the day the malfunction was recorded in the aircraft maintenance log and/or record.

The letter designators are inserted adjacent to Column 2.

23. Electronic fault alerting system - General

New generation aircraft display system fault indications to the flight crew by use of computerized display systems. Each aircraft manufacturer has incorporated individual design philosophies in determining the data that would be represented. The following are customized definitions (specific to each manufacturer) to help determine the level of messages affecting the aircraft's dispatch status. When preparing the MEL document, operators are to select the proper Definition No. 23 for their aircraft, if appropriate.

a. BOEING (B-757/767, B-747-400, B-777)

Boeing airplanes equipped with Engine Indicating and Crew Alerting Systems (EICAS), provide different priority levels of system messages (WARNING, CAUTION, ADVISORY, STATUS and MAINTENANCE). Any messages that affects airplane dispatch status will be displayed at a STATUS message level or higher. The absence of an EICAS STATUS or higher level (WARNING, CAUTION, ADVISORY) indicates that the system/component is operating within its approved operating limits or tolerances.

System conditions that result only in a maintenance level message, i.e. no correlation with a higher level EICAS message,

CESSNA - (TURBOPROP) 421C STC SA1361SO

Definitions

do not affect dispatch and do not require action other than as addressed within an operators standard maintenance program.

b. DOUGLAS (MD-11)

Some Douglas aircraft are equipped with an alerting function which is a subsystem within the Electronic Instrument System (EIS). The alerting function provides various levels of system condition alerts (WARNING, CAUTION, ADVISORY, MAINTENANCE and STATUS).

Alerts that affect aircraft dispatch will include WARNING, CAUTION, STATUS or MAINTENANCE level. MAINTENANCE alerts are displayed on the status page of the EIS display panel under the maintenance heading.

A MAINTENANCE alert on the EIS indicates the presence of a system fault which can be identified by the Central Fault Display System (CFDS) interrogation. The systems are designed to be fault tolerant, however, for any MAINTENANCE alert, the MEL must be verified for dispatch purposes.

c. AIRBUS (A-300-600, A-310, A-320/319/321, A-330, A-340)

Airbus aircraft equipped with Electronic Centralized Aircraft Monitoring (ECAM) provide different levels of system condition messages (WARNING, CAUTION, STATUS, and ADVISORY). A-320/319/321, A-330, and A-340 also provide MAINTENANCE status messages.

Any message that effects airplane dispatchability will normally be at the WARNING, CAUTION or STATUS level. MAINTENANCE messages (A-320/319/321, A-330, and A-340 only) are also indicated on ECAM Status Page below the white Maintenance label.

A MAINTENANCE status (Class II) message on ECAM indicates the presence of a system fault which can be identified by CFDS (A-320/319/321) or CMS (A-330/A-340) interrogation. The systems are designed to be fault tolerant, however for any MAINTENANCE status (Class II) message, the A-320/319/321 MEL must be verified for dispatch capability. For the A-330 and A-340, MAINTENANCE status messages do not affect dispatch.

d. FOKKER (FK-100)

CESSNA - (TURBOPROP) 421C STC SA1361SO

#### Definitions

Fokker aircraft are equipped with Multi Function Display System (MFDS) which provides electronic message referring to the different priority levels of system information (WARNING (red), CAUTION (amber), AWARENESS (cyan) AND STATUS (white). Any messages that affects aircraft dispatch will be at the WARNING, CAUTION or AWARENESS level. In these cases the MEL must be verified for dispatch capability and maintenance may be required.

System conditions that only require maintenance are not presented on the flight deck. These maintenance indications/messages may be presented on the Maintenance & Test Panel (MAP) or the Centralized Fault Display Unit (CFDU) and by dedicated Built In Test Evaluation (BITE) of systems.

24. "Administrative control item" means an item listed by the operator in the MEL for tracking and informational purposes. It may be added to an operator's MEL by approval of the Principal Operations Inspector provided no relief is granted, or provided conditions and limitations are contained in an approved document (i.e. Structural Repair Manual, airworthiness directive, etc.). If relief other than that granted by an approved document is sought for an administrative control item, a request must be submitted to the Administrator. If the request results in review and approval by the FOEB, the item becomes an MMEL item rather than an administrative control item.

25. "\*\*\*\*" symbol in Column 1 indicates an item which is not required by regulation but which may have been installed on some models of aircraft covered by this MMEL. This item may be included on the operator's MEL after the approving office has determined that the item has been installed on one or more of the operator's aircraft. The symbol, however, shall not be carried forward into the operator's MEL. It should be noted that neither this policy nor the use of this symbol provide authority to install or remove an item from an aircraft.

26. "Excess Items" means those items that have been installed that are redundant to the requirements of the FARs.

27. "Day of Discovery" is the calendar day an equipment/instrument malfunction was recorded in the aircraft

FEDERAL AVIATION ADMINISTRATION  
MASTER MINIMUM EQUIPMENT LIST

Page: XIV  
Revision: 6  
Date: 01/31/95

CESSNA - (TURBOPROP) 421C STC SA1361SO

Definitions

maintenance log and or record. This day is excluded from the calendar days or flight days specified in the MMEL for the repair of an inoperative item of equipment. This provision is applicable to all MMEL items, i.e., categories "A, B, C, and D."

CESSNA - (TURBOPROP) 421C STC SA1361SO

Preamble  
(Effective 6/14/89)

The following is applicable for authorized certificate holders operating under Federal Aviation Regulations (FAR) Parts 121, 125, 129, 135: The FAR require that all equipment installed on an aircraft in compliance with the Airworthiness Standards and the Operating Rules must be operative. However, the Rules also permit the publication of a Minimum Equipment List (MEL) where compliance with certain equipment requirements is not necessary in the interests of safety under all operating conditions. Experience has shown that with the various levels of redundancy designed into aircraft, operation of every system or installed component may not be necessary when the remaining operative equipment can provide an acceptable level of safety. A Master Minimum Equipment List (MMEL) is developed by the FAA, with participation by the aviation industry, to improve aircraft utilization and thereby provide more convenient and economic air transportation for the public. The FAA approved MMEL includes those items of equipment related to airworthiness and operating regulations and other items of equipment which the Administrator finds may be inoperative and yet maintain an acceptable level of safety by appropriate conditions and limitations; it does not contain obviously required items such as wings, flaps, and rudders. The MMEL is the basis for development of individual operator MELs which take into consideration the operator's particular aircraft equipment configuration and operational conditions. Operator MELs, for administrative control, may include items not contained in the MMEL; however, relief for administrative control items must be approved by the Administrator. An operator's MEL may differ in format from the MMEL, but cannot be less restrictive than the MMEL. The individual operator's MEL, when approved and authorized, permits operation of the aircraft with inoperative equipment.

Equipment not required by the operation being conducted and equipment in excess of FAR requirements are included in the MEL with appropriate conditions and limitations. The MEL must not deviate from the Aircraft Flight Manual Limitations, Emergency Procedures or with Airworthiness Directives. It is important to remember that all equipment related to the airworthiness and the operating regulations of the aircraft not listed on the MMEL must be operative.



CESSNA - (TURBOPROP) 421C STC SA1361SO

Preamble  
(Effective 6/14/89)

Suitable conditions and limitations in the form of placards, maintenance procedures, crew operating procedures and other restrictions as necessary are specified in the MEL to ensure that an acceptable level of safety is maintained.

The MEL is intended to permit operation with inoperative items of equipment for a period of time until repairs can be accomplished. It is important that repairs be accomplished at the earliest opportunity. In order to maintain an acceptable level of safety and reliability the MMEL establishes limitations on the duration of and conditions for operation with inoperative equipment. The MEL provides for release of the aircraft for flight with inoperative equipment. When an item of equipment is discovered to be inoperative, it is reported by making an entry in the Aircraft Maintenance Record/Logbook as prescribed by FAR. The item is then either repaired or may be deferred per the MEL or other approved means acceptable to the Administrator prior to further operation. MEL conditions and limitations, do not relieve the operator from determining that the aircraft is in condition for safe operation with items of equipment inoperative.

When these requirements are met, an Airworthiness Release, Aircraft Maintenance Record/Logbook entry, or other approved documentation is issued as prescribed by FAR. Such documentation is required prior to operation with any item of equipment inoperative.

Operators are responsible for exercising the necessary operational control to ensure that an acceptable level of safety is maintained. When operating with multiple inoperative items, the interrelationships between those items and the effect on aircraft operation and crew workload will be considered.

Operators are to establish a controlled and sound repair program including the parts, personnel, facilities, procedures, and schedules to ensure timely repair.

WHEN USING THE MEL, COMPLIANCE WITH THE STATED INTENT OF THE PREAMBLE, DEFINITIONS, AND THE CONDITIONS AND LIMITATIONS SPECIFIED IN THE MEL IS REQUIRED.

CESSNA - (TURBOPROP) 421C STC SA1361SO

Guidelines for (O) & (M) Procedures

The FOEB has identified a need for certain procedures to provide an adequate level of safety while providing relief for the following items. These procedures must be established by the operator. The following guidelines are to help establish these required procedures.

- 21.1 (M) Maintenance procedure to ensure the valve is blocked in the open position.
- 21.6 (M) Maintenance procedure to ensure no fuel leaks or mechanical/ electrical faults exist which could be a hazard.
- 22.1 (M) Maintenance procedure to ensure no electrical or mechanical fault exists which could have an adverse effect on any flight control function.
- 22.2 (M) Maintenance procedure to ensure no electrical or mechanical fault exists which could have an adverse effect on any flight control function.
- 23.4 (O) Operations procedure to ensure passengers are appropriately briefed.
- 27.1 (M) Maintenance procedure to ensure failure of electric trim will not interfere with manual trim operation.
- 28.1 (O) Operations procedure to determine fuel quantity on board the aircraft.
- 31.2 (O) Operations procedure to record elapsed flight time.
- 33.3 (O) Operations procedure to ensure passengers are appropriately briefed.

CESSNA - (TURBOPROP) 421C STC SA1361SO

Guidelines for (O) & (M) Procedures

- 34-20-1 (M) Maintenance procedure to ensure system is deactivated and secured.
  - 2 (O) Operations procedure to ensure TA and RA display is visible to the non-flying pilot and audio functions are operative on flying pilot side.
  - 3 (O) Operations procedure to ensure non-flying pilot monitors pilot's display.
    - (O) Operations procedure to ensure TA ONLY mode is selected and all TA functions/elements are operative.
  - 4 (O) Operations procedure to ensure all RA display/functions are operative.
- 34-21 (M) Maintenance procedure to ensure system is deactivated and secured.
- 34-22-1 (O) Operations procedure to ensure crew awareness of minimum altitudes and aircraft performance.
  - (O) Operations procedure to ensure crew awareness of minimum altitudes and aircraft performance.
  - (O) Operations procedure to ensure crew awareness of minimum altitudes and aircraft performance.
- 34-23-1 (O) Operations procedure to ensure crew awareness.
  - 2 (O) Operations procedure to ensure crew awareness of minimum altitudes and aircraft performance.
  - 3 (O) Operations procedure to ensure crew awareness.
  - 6 (O) Operations procedure to ensure crew awareness of missing advisory callouts.

## U.S. DEPARTMENT OF TRANSPORTATION

## MASTER MINIMUM EQUIPMENT LIST

## FEDERAL AVIATION ADMINISTRATION

AIRCRAFT:

REVISION NO: 4

PAGE:

CESSNA - (TURBOPROP) 421C STC SA1361SO

DATE: 11/14/96

21-1

1.			2. NUMBER INSTALLED		
SYSTEM & SEQUENCE NUMBERS		ITEM	3. NUMBER REQUIRED FOR DISPATCH		
-----			4. REMARKS OR EXCEPTIONS		
21 AIR CONDITIONING					
1.	Manual Dump System	C	1	0	(M)May be inoperative for unpressurized flight provided dump valve is secured in the open position.
2.	Cabin Altitude/ Pressure Differential Indicator	C	1	0	May be inoperative for unpressurized flight.
3.	Cabin Rate of Climb	C	1	0	May be inoperative for pressurized flight provided Cabin Altitude/ Pressure Differential Indicator is operative.
					OR
		C	1	0	May be inoperative for unpressurized flight.
4.	Cabin Altitude Warning System	C	1	0	May be inoperative for unpressurized flight.
					OR
		C	1	0	May be inoperative for pressurized flight provided aircraft remains at or below 10,000 ft. MSL.
5.	Cabin Pressurization Control System	C	1	0	May be inoperative for unpressurized flight.
6.	Heater	C	1	0	(M)

U.S. DEPARTMENT OF TRANSPORTATION

MASTER MINIMUM EQUIPMENT LIST

FEDERAL AVIATION ADMINISTRATION

AIRCRAFT:

REVISION NO: 4

PAGE:

CESSNA - (TURBOPROP) 421C STC SA1361SO

DATE: 11/14/96

21-2

1.		2. NUMBER INSTALLED			4. REMARKS OR EXCEPTIONS
SYSTEM & SEQUENCE NUMBERS	ITEM			3. NUMBER REQUIRED FOR DISPATCH	
-----					
21	AIR CONDITIONING				
7.	Heater Blower	C	1	0	May be inoperative provided: a) Use of heater or windshield defogging is not necessary on the ground, and b) Heater is turned off prior to landing.
8.	Cooling System	C	1	0	
9.	Cabin Pressure Regulator Valve	C	1	0	May be inoperative for unpressurized flight.

U.S. DEPARTMENT OF TRANSPORTATION

MASTER MINIMUM EQUIPMENT LIST

FEDERAL AVIATION ADMINISTRATION

AIRCRAFT:

REVISION NO: 4

PAGE:

CESSNA - (TURBOPROP) 421C STC SA1361SO

DATE: 11/14/96

22-1

1.		2. NUMBER INSTALLED			4. REMARKS OR EXCEPTIONS
SYSTEM & SEQUENCE NUMBERS	ITEM			3. NUMBER REQUIRED FOR DISPATCH	
22 AUTO FLIGHT					
1. Autopilot	C	1	0	(M)As required by FAR.	
2. Yaw Damper	C	1	0	(M)	

## U.S. DEPARTMENT OF TRANSPORTATION

## MASTER MINIMUM EQUIPMENT LIST

## FEDERAL AVIATION ADMINISTRATION

AIRCRAFT:

REVISION NO: 4

PAGE:

CESSNA - (TURBOPROP) 421C STC SA1361SO

DATE: 11/14/96

23-1

1.		2. NUMBER INSTALLED		3. NUMBER REQUIRED FOR DISPATCH		4. REMARKS OR EXCEPTIONS
SYSTEM & SEQUENCE NUMBERS	ITEM					
1. Communications Equipment (VHF, HF, UHF)	C	-	-	-	-	As required by FAR.
2. Cockpit Speakers	C	2	0	0	0	May be inoperative provided two operative headsets are available to the flight crew.
3. Audio Amplifiers	C	2	0	0	0	May be inoperative provided two operative headsets are available to the flight crew.
4. Passenger Address System						
1) Passenger Configuration	B	1	0	0	0	(O)May be inoperative provided alternate, normal and emergency procedures, and/or operating restrictions are established and used.
2) Cargo Configuration	D	1	0	0	0	
5. Cockpit Voice *** Recorder (CVR) System.	A	1	0	0	0	May be inoperative provided repairs are made within three flight days.
6. Boom Microphones						
1) Cockpit Voice Recorder Equipped to Record Boom Microphone per FRR 135.151(d)	A	-	0	0	0	May be inoperative provided repairs are made within three flight days.
2) Cockpit Voice Recorder Not Equipped To Record Boom Microphone	D	-	0	0	0	

U.S. DEPARTMENT OF TRANSPORTATION

MASTER MINIMUM EQUIPMENT LIST

FEDERAL AVIATION ADMINISTRATION

AIRCRAFT:

REVISION NO: 4

PAGE:

CESSNA - (TURBOPROP) 421C STC SA1361SO

DATE: 11/14/96

24-1

SYSTEM & SEQUENCE NUMBERS		1.	2. NUMBER INSTALLED			4. REMARKS OR EXCEPTIONS
ITEM				3. NUMBER REQUIRED FOR DISPATCH		
24	ELECTRICAL POWER					
1.	D.C. Loadmeter	B	2	1	One may be inoperative provided corresponding Generator Warning Light is operative.	
2.	D.C. Generator Warning Light	B	2	1	One may be inoperative provided corresponding Generator Loadmeter is operative.	



## U.S. DEPARTMENT OF TRANSPORTATION

## MASTER MINIMUM EQUIPMENT LIST

## FEDERAL AVIATION ADMINISTRATION

AIRCRAFT:

REVISION NO: 4

PAGE:

CESSNA - (TURBOPROP) 421C STC SA1361SO

DATE: 11/14/96

25-1

1.		2. NUMBER INSTALLED		3. NUMBER REQUIRED FOR DISPATCH		4. REMARKS OR EXCEPTIONS
SYSTEM & SEQUENCE NUMBERS	ITEM					
25	EQUIPMENT/FURNISHINGS					
1.	Cockpit Shoulder Harness	C	2	1		Right side may be inoperative provided seat remains unoccupied.
2.	Passenger Seats	C	-	0		May be inoperative provided: a) Affected seat does not block emergency egress to the aisle or exit and b) Affected seat is blocked and placarded "DO NOT OCCUPY".
						NOTE:
						1. A seat with an inoperative seatbelt or shoulder harness is considered to be inoperative.
						2. A seat with an inoperative recline mechanism is considered to be inoperative if the seat back cannot be secured in the upright position.
3.	Flotation Devices	D	-	-		Any in excess of those required by FAR may be inoperative.
4.	ELT	C	1	0		May be inoperative for published scheduled flights in scheduled air carrier service.
						OR
		C	1	0		As required by FAR.
5.	First Aid Kits	D	-	-		Any in excess of those required by FAR may be incomplete or missing provided required distribution is maintained.

U.S. DEPARTMENT OF TRANSPORTATION

MASTER MINIMUM EQUIPMENT LIST

FEDERAL AVIATION ADMINISTRATION

AIRCRAFT:

REVISION NO: 4

PAGE:

CESSNA - (TURBOPROP) 421C STC SA1361SO

DATE: 11/14/96

25-2

1.		2. NUMBER INSTALLED		4. REMARKS OR EXCEPTIONS
SYSTEM & SEQUENCE NUMBERS	ITEM		3. NUMBER REQUIRED FOR DISPATCH	
25	EQUIPMENT/FURNISHINGS			
6.	Passenger Convenience Items	-	-	Passenger convenience items, as expressed in this MMEL, are those related to passenger convenience, comfort or entertainment such as but not limited to, galley equipment, movie equipment, ash trays, stereo equipment, overhead reading lamps, etc. Items addressed elsewhere in this document shall not be included. (M) and (O) procedures may be required in the air carrier's appropriate document.

U.S. DEPARTMENT OF TRANSPORTATION

MASTER MINIMUM EQUIPMENT LIST

FEDERAL AVIATION ADMINISTRATION

AIRCRAFT:

REVISION NO: 4

PAGE:

CESSNA - (TURBOPROP) 421C STC SA1361SO

DATE: 11/14/96

26-1

1.		2. NUMBER INSTALLED		3. NUMBER REQUIRED FOR DISPATCH	4. REMARKS OR EXCEPTIONS
SYSTEM & SEQUENCE NUMBERS	ITEM				
26	FIRE PROTECTION				
1.	Portable Fire Extinguisher	D	-	-	Any in excess of those required by FAR may be inoperative or missing provided: a) The inoperative fire extinguisher is tagged inoperative, removed from the installed location, and placed out of sight so it can not be mistaken for a functional unit and b) Required distribution is maintained.

U.S. DEPARTMENT OF TRANSPORTATION

MASTER MINIMUM EQUIPMENT LIST

FEDERAL AVIATION ADMINISTRATION

AIRCRAFT:

REVISION NO: 4

PAGE:

CESSNA - (TURBOPROP) 421C STC SA1361SO

DATE: 11/14/96

27-1

1.		2. NUMBER INSTALLED			3. NUMBER REQUIRED FOR DISPATCH	4. REMARKS OR EXCEPTIONS
SYSTEM & SEQUENCE NUMBERS	ITEM					
27	FLIGHT CONTROLS					
1.	Electric Elevator Trim System	C	1	0		(M)May be inoperative provided manual trim is operative and unaffected.
2.	Flap Position Indicator	C	1	0		May be inoperative provided: a) Flaps are visually checked for full travel and flap operation is not affected and b) Flaps are visually checked full up or for proper setting prior to each departure.
3.	Trim Tab Indicators (Aileron Elevator Rudder)	C	3	0		May be inoperative provided: a) Tab is visually checked for full range of operation. b) Tab operation is not impaired and c) Tab is positioned to neutral prior to each departure and neutral position is verified by visual inspection.

U.S. DEPARTMENT OF TRANSPORTATION

MASTER MINIMUM EQUIPMENT LIST

FEDERAL AVIATION ADMINISTRATION

AIRCRAFT:

REVISION NO: 4

PAGE:

CESSNA - (TURBOPROP) 421C STC SA1361SO

DATE: 11/14/96

28-1

1.		2. NUMBER INSTALLED			4. REMARKS OR EXCEPTIONS
SYSTEM & SEQUENCE NUMBERS	ITEM			3. NUMBER REQUIRED FOR DISPATCH	
28 FUEL					
1. Fuel Quantity Indicators	C	2	1		(O)One may be inoperative provided a reliable means is established to determine that fuel quantity on board meets the regulatory requirements for the intended flight.
2. Fuel Low Level Annunciator Lights	C	2	0		

## U.S. DEPARTMENT OF TRANSPORTATION

## MASTER MINIMUM EQUIPMENT LIST

## FEDERAL AVIATION ADMINISTRATION

AIRCRAFT:

REVISION NO: 4

PAGE:

CESSNA - (TURBOPROP) 421C STC SA1361SO

DATE: 11/14/96

30-1

1.		2. NUMBER INSTALLED		3. NUMBER REQUIRED FOR DISPATCH		4. REMARKS OR EXCEPTIONS
SYSTEM & SEQUENCE NUMBERS	ITEM					
30	ICE AND RAIN PROTECTION					
1.	Pitot Heaters	B	2	0		Right Pitot Heater may be inoperative.  Left Pitot Heater may be inoperative except for: a) IFR passenger carrying operations and b) Flight in known or forecast icing conditions.
2.	Surface Deicing System (Wing, Vertical and Horizontal Stabilizer)	C	1	0		May be inoperative provided flight is not operated in known or forecast icing conditions.
3.	Heated Windshield System	C	1	0		May be inoperative provided flight is not operated in known or forecast icing conditions.
4.	Propeller Deicing Systems	C	2	0		May be inoperative provided flight is not operated in known or forecast icing conditions.
5.	Stall Warning/ Angle of Attack Heater	C	1	0		May be inoperative provided flight is not operated in known or forecast icing conditions.
6.	Alcohol Windshield Deice System	C	1	0		May be inoperative provided flight is not operated in known or forecast icing conditions.

U.S. DEPARTMENT OF TRANSPORTATION

MASTER MINIMUM EQUIPMENT LIST

FEDERAL AVIATION ADMINISTRATION

AIRCRAFT:

REVISION NO: 4

PAGE:

CESSNA - (TURBOPROP) 421C STC SA1361SO

DATE: 11/14/96

31-1

1.		2. NUMBER INSTALLED			4. REMARKS OR EXCEPTIONS
SYSTEM & SEQUENCE NUMBERS	ITEM			3. NUMBER REQUIRED FOR DISPATCH	
31	INDICATING/RECORDING SYSTEMS				
1.	Clock with sweep second hand, or electric digital clock	C	1	0	May be inoperative for VFR operations.
2.	Flight Hour Recorder	C	1	0	(0)
3.	Flight Data *** Recorder (FDR)	B	1	0	May be inoperative provided Cockpit Voice Recorder (CVR) is operative.

## U.S. DEPARTMENT OF TRANSPORTATION

## MASTER MINIMUM EQUIPMENT LIST

## FEDERAL AVIATION ADMINISTRATION

AIRCRAFT:

REVISION NO: 4

PAGE:

CESSNA - (TURBOPROP) 421C STC SA1361SO

DATE: 11/14/96

33-1

1.		2. NUMBER INSTALLED			4. REMARKS OR EXCEPTIONS
SYSTEM & SEQUENCE NUMBERS	ITEM				
33	LIGHTS				
1.	Cockpit/ Flight Deck/ Flight Compartment and Instrument Lighting System	C	-	-	Individual lights may be inoperative provided remaining lights are: a) Sufficient to clearly illuminate all required instruments, controls, and other devices for which it is provided, b) Positioned so that direct rays are shielded from flight crewmembers eyes, and c) Lighting configuration and intensity is acceptable to the flight crew.
2.	Cabin Lights	C	-	-	May be inoperative provided lighting configuration is acceptable to the flight crew.
3.	Passenger Notice Sign (No Smoking - Fasten Seat Belt)	C	1	0	(O)May be inoperative provided appropriate verbal briefings are given to passengers.
4.	Anti-collision Beacon Light System	B	1	0	May be inoperative for day operations.
5.	Strobe Light System	C	1	0	
6.	Landing Lights	C	-	0	May be inoperative for day operations.
7.	Position Light System	C	1	0	May be inoperative for day operations.
8.	Taxi Light	C	1	0	
9.	Logo Light	C	2	0	



U.S. DEPARTMENT OF TRANSPORTATION

MASTER MINIMUM EQUIPMENT LIST

FEDERAL AVIATION ADMINISTRATION

AIRCRAFT:

REVISION NO: 4

PAGE:

CESSNA - (TURBOPROP) 421C STC SA1361SO

DATE: 11/14/96

33-2

1.		2. NUMBER INSTALLED		3. NUMBER REQUIRED FOR DISPATCH	4. REMARKS OR EXCEPTIONS
SYSTEM & SEQUENCE NUMBERS	ITEM				
33 LIGHTS					
10. Wing Ice Lights	C	-	0		May be inoperative provided a portable lamp/light of adequate capacity for wing and/or control surface inspection is available for night operations in icing conditions.

## U.S. DEPARTMENT OF TRANSPORTATION

## MASTER MINIMUM EQUIPMENT LIST

## FEDERAL AVIATION ADMINISTRATION

AIRCRAFT:

REVISION NO: 4

PAGE:

CESSNA - (TURBOPROP) 421C STC SA1361SO

DATE: 11/14/96

34-1

1.			2. NUMBER INSTALLED		
SYSTEM & SEQUENCE NUMBERS		ITEM		3. NUMBER REQUIRED FOR DISPATCH	
				4. REMARKS OR EXCEPTIONS	
34 NAVIGATION					
1.	Altimeters, Adjustable for barometric pressure	B	-	1	May be inoperative on right side.  NOTE: Where a servoed electric altimeter is installed, a functioning pneumatic indicator is required.
2.	Airspeed Indicators	C	2	1	May be inoperative on right side  NOTE: Where a servoed electric airspeed is installed, a functioning pneumatic indicator is required.
3.	Gyroscopic Pitch and Bank Indicator Systems	B	2	1	May be inoperative on right side.
4.	Gyroscopic Rate of Turn/Slip Skid Indicators	B	-	1	May be inoperative on right side.
		B	-	0	May be inoperative on left side except for IFR, passenger carrying VFR Over-The-Top, and passenger carrying VFR night flights.
5.	Gyroscopic Directional Indicator Systems	B	-	1	May be inoperative on right side
6.	Vertical Speed Indicators	B	-	1	May be inoperative on right side.
		B	-	0	May be inoperative on left side except for IFR passenger carrying operations.
7.	ATC Transponders and Automatic Altitude Reporting Systems	D	-	-	Any in excess of those required by FAR may be inoperative.

U.S. DEPARTMENT OF TRANSPORTATION

MASTER MINIMUM EQUIPMENT LIST

FEDERAL AVIATION ADMINISTRATION

AIRCRAFT:

REVISION NO: 4

PAGE:

CESSNA - (TURBOPROP) 421C STC SA1361SO

DATE: 11/14/96

34-2

1.		2. NUMBER INSTALLED			4. REMARKS OR EXCEPTIONS
SYSTEM & SEQUENCE NUMBERS	ITEM				
34	NAVIGATION				
8.	Navigation Equipment (VOR/ILS, Loran, Omega/VLF, INS, Doppler, RNAV, GPS)	C	-	-	As required by FAR.
9.	Weather Radar/Thunderstorm Detection Equipment	C	1	0	As required by FAR.
10.	Marker Beacon	C	1	0	May be inoperative provided approach procedure does not require its use.
11.	Flight Director	C	1	0	
12.	Radar Altimeter	C	1	0	
13.	Altitude Encoder				Combined with ATA 34.7.
14.	DME	C	1	0	As required by FAR.
15.	Standby Attitude *** Indicator	C	1	0	
16.	ADF	C	1	0	As required by FAR.
17.	RMI	C	1	0	
18.	Altitude Alerter ***	C	1	0	

## U.S. DEPARTMENT OF TRANSPORTATION

## MASTER MINIMUM EQUIPMENT LIST

## FEDERAL AVIATION ADMINISTRATION

AIRCRAFT:

REVISION NO: 4

PAGE:

CESSNA - (TURBOPROP) 421C STC SA1361SO

DATE: 11/14/96

34-3

SYSTEM & SEQUENCE NUMBERS	ITEM	1.		2. NUMBER INSTALLED		3. NUMBER REQUIRED FOR DISPATCH	4. REMARKS OR EXCEPTIONS
34	NAVIGATION						
19.	Nonstabilized Magnetic Compass	B	1	0			May be inoperative provided any combination of three gyro or INS (IRU) stabilized compass systems are operative.
							OR
		B	1	0			May be inoperative provided: a) Any combination of two gyro or INS stabilized compass systems are operative and b) Aircraft is operated with dual independent navigation capability and under positive radar control by ATC on the enroute portion of the flight.
							OR
		B	1	0			May be inoperative for flights that are entirely within areas of magnetic unreliability provided at least two stabilized directional gyro systems are installed, operative, and used in conjunction with approved free gyro navigation techniques.

U.S. DEPARTMENT OF TRANSPORTATION

MASTER MINIMUM EQUIPMENT LIST

FEDERAL AVIATION ADMINISTRATION

AIRCRAFT:

REVISION NO: 4

PAGE:

CESSNA - (TURBOPROP) 421C STC SA1361SO

DATE: 11/14/96

34-4

1.		2. NUMBER INSTALLED		3. NUMBER REQUIRED FOR DISPATCH		4. REMARKS OR EXCEPTIONS
SYSTEM & SEQUENCE NUMBERS	ITEM					
34	NAVIGATION					
20.	Traffic Alert					
***	Collision Avoidance System (TCAS II)					
1)	TCAS System	C	-	0		(M)May be inoperative provided the system is deactivated and secured.
2)	Combined TA and	C	2	1		(O)One may be inoperative on the non-flying pilot side provided:
***	RA Dual Displays					a) TA and RA elements and audio functions are operative on flying pilot side and b) TA and RA display indications are visible to the non-flying pilot.
3)	Resolution	C	2	1		(O)One may be inoperative on non- flying pilot side.
	Advisory (RA)					
	Display System(s)	C	-	0		(O)May be inoperative provided:
						a) All Traffic Alert (TA) display elements and voice command audio functions are operative and
4)	TA Display	C	-	0		(O)May be inoperative provided all installed RA display and audio functions are operative.
	System(s)					
21.	Traffic Alert	C	1	0		(M)May be inoperative provided the system is deactivated and secured.
***	Collision Avoidance System (TCAS I)					

## U.S. DEPARTMENT OF TRANSPORTATION

## MASTER MINIMUM EQUIPMENT LIST

## FEDERAL AVIATION ADMINISTRATION

AIRCRAFT:

REVISION NO: 4

PAGE:

CESSNA - (TURBOPROP) 421C STC SA1361SO

DATE: 11/14/96

34-5

1.		2. NUMBER INSTALLED		3. NUMBER REQUIRED FOR DISPATCH		4. REMARKS OR EXCEPTIONS
SYSTEM & SEQUENCE NUMBERS	ITEM					
34	NAVIGATION					
22.	Ground Proximity					
***	Warning System (GPWS)					
1)	Modes 1-4	A	-	0		(O)May be inoperative provided: a) Alternate procedures are established and used and b) Repairs are made within two flight days.
2)	Test Mode	A	1	0		May be inoperative provided: a) The GPWS is considered inoperative and b) Repairs are made within two flight days.
3)	Glideslope Deviation (Mode 5)	B	2	0		
4)	Advisory	C	-	0		(O)May be inoperative provided alternate procedures are established and used.
***	Callouts					
5)	Windshear Mode	C	-	0		(O)May be inoperative provided alternate procedures are established and used.
***						

## U.S. DEPARTMENT OF TRANSPORTATION

## MASTER MINIMUM EQUIPMENT LIST

## FEDERAL AVIATION ADMINISTRATION

AIRCRAFT:

REVISION NO: 4

PAGE:

CESSNA - (TURBOPROP) 421C STC SA1361SO

DATE: 11/14/96

34-6

1.		2. NUMBER INSTALLED			3. NUMBER REQUIRED FOR DISPATCH	4. REMARKS OR EXCEPTIONS
SYSTEM & SEQUENCE NUMBERS	ITEM					
34	NAVIGATION					
23.	Flight Profile					
***	Advisory System (FPA)					
1)	Gear Mode	A	1	0	(O)May be inoperative provided:	
					a) Alternate procedures are	
					established and used and	
					b) Repairs are made within two	
					flight days.	
2)	Minimums Mode	A	1	0	(O)May be inoperative provided:	
					a) Alternate procedures are	
					established and used and	
					b) Repairs are made within two	
					flight days.	
3)	Radio Altitude	A	1	0	(O)May be inoperative provided:	
	Mode				a) Alternate procedures are	
					established and used and	
					b) Repairs are made within two	
					flight days.	
4)	Test Mode	A	1	0	May be inoperative provided:	
					a) The FPA is considered	
					inoperative and	
					b) Repairs are made within two	
					flight days.	
5)	Glideslope	B	1	0		
	Deviation Mode					
6)	Advisory	C	-	0	(O)May be inoperative provided	
	Callouts				alternate procedures are	
					established and used.	

U.S. DEPARTMENT OF TRANSPORTATION

MASTER MINIMUM EQUIPMENT LIST

FEDERAL AVIATION ADMINISTRATION

AIRCRAFT:

REVISION NO: 4

PAGE:

CESSNA - (TURBOPROP) 421C STC SA1361SO

DATE: 11/14/96

35-1

1.		2. NUMBER INSTALLED			4. REMARKS OR EXCEPTIONS
SYSTEM & SEQUENCE NUMBERS	ITEM			3. NUMBER REQUIRED FOR DISPATCH	
35	OXYGEN				
1.	Oxygen System (Passenger)	C	-	-	As required by FAR.



U.S. DEPARTMENT OF TRANSPORTATION

MASTER MINIMUM EQUIPMENT LIST

FEDERAL AVIATION ADMINISTRATION

AIRCRAFT:

REVISION NO: 4

PAGE :

CESSNA - (TURBOPROP) 421C STC SA1361SO

DATE: 11/14/96

52-1

1.

2. NUMBER INSTALLED

SYSTEM &  
SEQUENCE  
NUMBERS

ITEM

### 3. NUMBER REQUIRED FOR DISPATCH

4. REMARKS OR EXCEPTIONS

52 DOORS

## 1. Door Seal

C

1

0

May be inoperative for  
unpressurized flight.

U.S. DEPARTMENT OF TRANSPORTATION

MASTER MINIMUM EQUIPMENT LIST

FEDERAL AVIATION ADMINISTRATION

AIRCRAFT:

REVISION NO: 4

PAGE:

CESSNA - (TURBOPROP) 421C STC SA1361SO

DATE: 11/14/96

61-1

1.		2. NUMBER INSTALLED			4. REMARKS OR EXCEPTIONS
SYSTEM & SEQUENCE NUMBERS	ITEM		3. NUMBER REQUIRED FOR DISPATCH		
61	PROPELLERS				
1.	Propeller Synchrophaser	C	1	0	